



#### Fast defrosting

Fast defrosting significantly reduces defrosting periods with minimal temperature variations.

# MED 520

## ULTIMATE

according to DIN 13277



- **PRO-ACTIVE-Control:** Permanent, proactive monitoring of the performance data and alerts in the case of deviations – so that you can take countermeasures in good time before a fault threatens your chilled goods; world's most accurate temperature control in refrigerated areas thanks to two standard PT-1000 sensors.
- **Touch-Display,** elegant glass design, capacitive.
- **Access control** with protocol.
- **Graphical display** of the temperature curve and min/max temperature
- **External housing** made from galvanised sheet steel (rustproof), with white, anti-scratch powder coating. Length of the plug cable: approx. 3 m.
- **Equipped with castors.**
- **Interior** made from smooth aluminium with colourless protective coating. Gibs (every 15 mm) for flexible interior arrangement.
- **Interior consists** of twelve black drawers with stops, on roller runners. There are two adjustable length dividers and twelve adjustable cross dividers per drawer. Storage surface per drawer = 0.23 m<sup>2</sup>.
- **Extra-thick 70-mm insulation,** made from high-quality, compression-moulded and environmentally friendly material. Energy saving.

- **Self-Closing-Door** with easy-to-replace plastic magnetic seal frame, lockable.
- **Door hinge** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.
- **Forced-air cooling,** switches off automatically when you open the door, ensures a uniform temperature and minimizes temperature deviations.
- **Automatic fast defrosting** thanks to time-limited and temperature-monitored reversal of the refrigerant circuit.
- **Condensate evaporation** in stainless steel heated dish beneath the refrigerator floor.
- **Digital data documentation** readable via PC-KIT-NET or USB interface and software KIRSCH Datanet.
- **Warning functions** with visual and audible alarm signal in the case of temperature deviations and power failure. In the case of power failure, the monitoring unit remains in operation for approx. 30 hours on battery power.
- **Alarms** can be forwarded by network or potential-free contact.
- **Antifreeze** against sub-zero temperatures.
- **Ventilation-enforced refrigerating machine,** hermetically sealed, energy saving, low noise, easy to service.

## Specification

Capacity	500 litres
Temperature setting	approx. +2 °C to +15 °C
Voltage	220 – 240 V, 50 Hz
Power consumption	260 watts
Normal consumption	1.50 kWh/24 h
Admissible ambient temperature	from +10 °C to +38 °C
Heat emission (max.)	560 watts
Exterior dimensions (including door handle and distance from wall)	w x d x h = 77 x 76 x 195.5 cm
Interior dimensions	w x d x h = 60 x 57 x 140 cm (usable depth 10 cm)
Exterior dimensions with door open at 90°	w x d = 77 x 144 cm
Drawer inner dimensions	w x d x h = 57.3 x 39 x 5.6 cm
Max. load drawer	24 kg
Weight	Net weight 145 kg, gross weight 168 kg

(measured values based on Eccol RG00a)

## Optional equipment

- **Glass door with lock.**
- **LED-Illumination** mounted on side wall.
- **Top drawer** can be locked.
- **Adjustable** feet to compensate uneven floors.
- **Additional length and cross dividers.**
- **Shelf** w x d = 59.7 x 45 cm on rails or overlays instead of drawer (max. load: 40 kg).
- **Condensate container** can be emptied manually if no condensation is required (e.g., in an operating theatre).
- **60 Hz cooling machine** upon request
- **Vario Suport,** Storage Shelf on roller runners.
- **GSM-Module** for alarm text message transmission (e.g., to a mobile phone).
- **Temperature documentation:**
  - 4-pin PT 100 or PT 1000 temperature sensor, class 1/3 B, including built-in reference body.
  - Mechanical pen-recording thermometer with two waxed paper strips.