

1 drawer and 2 shelves

(Drawers are currently available only in black color)

Minimum/maximum
temperature memory

Standalone or undercounter
installation

potential-free contact/
RJ 45 socket by optional
PC-KIT-NET

Rapid freezing cycle


Visual and
acoustic
alarm signal

Key switch

Digital temperature display

Low-noise compressor

USB-Port for reading out data



Low-noise compressor

Reduces noise to 40 dB (corresponds to noise level I; sounds perception: whisper).



Power package

High-performance freezer for standalone or undercounter installation (up to -25 °C).

FROSTER MED 95

PRO-ACTIVE



- **PRO-ACTIVE-Control:** Permanent, proactive monitoring of the performance data and alerts in the case of deviations – so that you can take countermeasures in good time before a fault threatens your chilled goods; world's most accurate temperature control in refrigerated areas thanks to two standard PT-1000 sensors
- **External housing** made from galvanised sheet steel (rustproof), with white, anti-scratch powder coating. Length of the plug cable: approx. 2.8 m.
- **Adjustable feet** positioned at the front to compensate uneven floors.
- **Interior** made from impact-resistant, white plastic with moulded-in shelves.
- **Interior consists** of one black drawer with stop and two plasticcoated shelves. There is one adjustable length divider and six adjustable cross dividers per drawer. Storage surface per drawer = 0.13 m².
- **Extra-thick 50-mm insulation**, made from high-quality, compression-moulded and environmentally friendly material. Energy saving.
- **Door** with easy-to-replace plastic magnetic seal frame, lockable.

- **Door hinge** on the right-hand side (by default, see illustration), or the left-hand side, can be retrofitted.
- **Manual defrosting.** Removable condensation container.
- **Key switch** protected control panel against tampering. Membrane keyboard with digital temperature display and minimum/maximum temperature memory.
- **Warning functions** with visual and audible alarm signal in the case of temperature deviations and power failure.
- **Alarms** can be forwarded using a potential-free contact (e.g., to a mobile phone with optional GSM-Module or to a control centre).
- **Data documentation** can be read via USB interface with KIRSCH Datanet software.
- **Rapid freezing cycle** ensures that the goods to be cooled are frozen quickly.
- **Ventilation-enforced refrigerating machine**, hermetically sealed, energy saving, low noise, easy to service. Inlet air and exhaust air flow through the ventilation slits at the front.
- **Low-noise compressor** reduces noise to 40 dB (corresponds to noise level I; sound perception: whisper).

Specification

| | |
|--|---|
| Capacity | 95 litres |
| Temperature setting | approx. -5 °C to -25 °C |
| Voltage | 220 – 240 V, 50 Hz |
| Power consumption | 123 watts |
| Normal consumption | 1,33 kWh/24 h |
| Admissible ambient temperature | from +10 °C to +32 °C |
| Heat emission (max.) | 162 watts |
| Exterior dimensions (including distance from wall) | w x d x h = 54 x 53.5 x 82 cm |
| Interior dimensions | w x d x h = 44 x 42 x 47 cm (usable depth 5 cm, usable width 2 cm less) |
| Exterior dimensions with door open at 90° | w x d = 54 x 105.5 cm |
| Shelf size | 43 x 36 cm |
| Drawer inner dimensions | w x d x h = 40 x 32 x 5.6 cm |
| Max. load drawer/shelf | 13 kg/25 kg |
| Weight | Net weight 50 kg, gross weight 54 kg |

(measured values based on Eccol RG00a)

Optional equipment

- **Tabletop** (exterior dimensions: 85 cm in height).
- **Decorative door frame** for attaching the customer's decorative plates.
- **Door fitting.**
- **Equipped with castors.**
- **Additional drawer or shelf.**
- **Additional length and cross dividers.**
- **Alarm** is also triggered in the case of power failure (visual and audible alarm); the monitoring unit remains in operation for approx. 30 hours on battery power.
- **GSM-Module** for alarm text message transmission (e.g., to a mobile phone).
- **Temperature documentation:**
 - PC-KIT-NET (network capable version)
 - 4-pin PT 100 or PT 1000 temperature sensor, class 1/3 B, including built-in reference body (measurement bottle or refrigerating block).
 - Mechanical pen-recording thermometer with two waxed paper strips.
- **60 Hz cooling machine** upon request